



NOTES

These drawings have been produced with reference to the CDM Regulations 2015. Please note that these are pre-construction phase drawings and should be subject to further design risk management as required in accordance with Regulation 9

Typical cross section of new active travel paths

- Minimum path width 3.0m within a minimum 4.0m wide corridor
- 0.5m wide green verge either side of path
- Stock fence or hedging along edges of corridor
- 2.5% cross fall or camber to drain to the edges
- 20mm surface course
- 60mm binder course
- Min. 150mm sub-base course
- geotextile below subject to ground conditions

Existing Public Right of Way (PRoW)

New active travel path or footway widening

New carriageway construction to accommodate active travel and agricultural vehicles

Existing road or track requiring repair and/or resurfacing

Buff anti-skid surface dressing or imprint asphalt in carriageway to highlight area/feature

Significant existing hedge retained and managed along existing path edge

New or enlarged verge / landscaped area

| REV | DATE | REVISION NOTE | BY |
|-----|----------|---------------------------------------|----|
| I | 07.01.22 | Virtual footway added on Water Street | MM |

PJA
Brew House - Jacob Street
Tower Hill - Bristol
BS2 0EQ - Tel: 0117 929 8856
Birmingham - Bristol
Exeter - London - Reading
pja.co.uk

CLIENT
Curry Rivel Parish Council

PROJECT
**Curry Rivel
Active Travel Routes
Study**

DRAWING TITLE
**Curry Rivel - West:
Potential interventions to
support active travel**

DRAWING ISSUE STATUS
INFORMATION

PJA JOB No. SUB-CODE
05725 - SK - 010 - PI

Revision Letter: P = Prelim / A = Approval / T = Tender / C = Construction
BIM DRAWING REFERENCE

| SCALE | DRAWN | REVIEWED | DATE |
|------------|-------|----------|----------|
| A1 @ 1:250 | MM | CS | 16/12/21 |